

worxguard MAX[®]

Floor protection for Painting, Renovating, Restoration, or Moving.



Floor protector

Brown Cardboard

Dimension: 915mm x 30m

Thickness: 0.5mm

Jointing tape

Brown Paper

Dimension: 60mm x 50m

- ▲ Breathable
- ▲ Save on damage repair
- ▲ Quick & easy to install
- ▲ Reusable and recyclable

Installation Instructions

Measure and Prepare



Before you begin it's important that you measure your space and work out exactly how much worxguard MAX[®] you will need. Calculate the square meterage and allow a little bit excess for cuts in odd-shaped areas.



When you are ready to install your floor or surface protection you should ensure that the space is clean and free from dust, dirt or anything that could cause scratches or other damage when covered.

For new floors, it is important that your floors are hard enough to withstand the traffic of the jobsite, however worxguard MAX[®] is designed with high breathability for surfaces that are still curing.

To Install

1. Roll Out



Unroll worxguard MAX[®] in an under-roll direction, with the paper laid flat against the floor and the roll positioned on top. If the material curls back toward you after being rolled out, gently bend it back on itself to release the fibre memory horizontally, which will help the sheet lay flat more easily.

2. Cut



Using a utility knife or other appropriate cutting tool, trim worxguard MAX[®] to the required length. Take care not to press or drag the blade through to the floor surface underneath when cutting through the paper.

3. Join



When covering larger areas, you may need to connect multiple sections of worxguard MAX[®] to achieve full surface protection.

Overlap adjoining edges by approximately 15 mm and secure the seams using a suitable jointing tape.

4. Perimeter



When taping down the perimeter of the surface protection, consult your flooring manufacturer or our Customer Service team to confirm the most suitable tape.

We recommend testing the tape in a small, inconspicuous area before application. Apply the tape so that half adheres to the worxguard MAX[®] paper and the other half seals to the floor surface.

5. Cleaning



To maintain the durability and potential reusability of worxguard MAX[®], any spills should be cleaned up as soon as possible while the protection is in place.

6. Reuse



Once the project is complete, remove any tape from the worxguard MAX[®] paper and clean the surface by sweeping or vacuuming away dust and debris. The material can then be rolled up and stored, ready for use on your next project.