

# METINNO VELLO®



**30**  
YEAR  
WARRANTY

## Features and Benefits

- Balanced Acoustics. High-NRC and High-CAC provide balance to room acoustics and sound attenuation.
- Excellent combination of noise reduction and sound attenuation.
- METINNO Vello® fulfills the formaldehyde emissions per EN 717-1 and achieves Class E1.
- Fine, monolithic texture. Reduces light fixtures and energy usage, and is part of indirect lighting.
- High impact and scratch-resistant; durable and cleanable surface.
- It is rated as Class 10 for mould prevention application as per ASTM D3273.
- Certified for Environmental Product Declaration (EPD) as per ISO 14025.
- Recommended to be used with METINNO Cliq® grid.
- Comes with a 30-year warranty.

## Surface Texture



## Absorption Coefficient

Frequency, Hz	125	250	500	1000	2000	4000	NRC*
19mm	0.45	0.50	0.75	0.85	0.80	0.65	0.75

\*Calculated to ASTM C 423-01

## Applications

Executive offices	Conference rooms
Reception areas	Lobbies
Classrooms	Corridors
Restaurants	Entertainment & gaming centers
Nurseries	

# Table of Performance



EN 13964 : 2014 + A1 : 2017



PRODUCT CERTIFIED FOR LOW VOC EMISSIONS



PRODUCT CERTIFIED FOR LOW VOC EMISSIONS



PRODUCT CERTIFIED FOR ENVIRONMENTAL PRODUCT DECLARATION



HIGH SOUND ABSORPTION



CEILING ATTENUATION CLASS



ANTI-MOULD & MILDEW / SAG RESISTANCE







FIRE RATING



HIGH RECYCLED CONTENT

Edge Detail	Product Code	Size (mm)	NRC	CAC	Anti-Mould & Mildew / Sag Resistance	Fire Rating	Recycled Content	VOC Emission
SQ	VE1260S	600*1200*19	0.75	37			83%	Low
TEG	VE1260T	600*1200*19	0.75	37			83%	Low
TEG	VE6060T	600*600*19	0.75	37			83%	Low

## METINNO CLIQ® GRID



## SPECIFICATION DETAILS

<p>METINNO Vello® Mineral Fibre Acoustic Ceiling Tiles meet specifications in accordance with ASTM E1264, EN13964, and AS 5637.1:2015.</p> <p><b>Materials Classification</b> Type: A Form: A2.1 Pattern: E, G</p> <p><b>Substrate and Surface Finish</b> Mineral fibre substrate laminated with fibreglass membrane and finished with factory-applied latex paint</p> <p><b>Thickness</b> 19mm</p> <p><b>Size</b> SQ 600*1200mm TEG 600*1200mm, 600*600mm</p> <p><b>Edge Detail Trim</b> Square, Tegular</p>	<p><b>Weight</b> 19mm [4.75 kg/m<sup>2</sup>]</p> <p><b>Noise Reduction Coefficient [NRC]</b> [0.75]</p> <p><b>Ceiling Attenuation Class [CAC]</b> [37 dB]</p> <p><b>Mould Prevention Application as per ASTM D3273</b> Rate 10: Resistant to mould growth</p> <p><b>Humidity Resistance</b> Maximum 99% RH / 40°C</p> <p><b>Colour</b> Standard White</p> <p><b>Fire Rating</b> Conforms with NCC Spec as tested to AS 5637.1:2015 - Group 1</p>	<p><b>Thermal Conductivity</b> <math>\lambda = 0.05 \text{ W/m}^2\text{K}</math></p> <p><b>Washability / Scrubbability as per ASTM D4828 &amp; D2486</b> Exceeds 1000 wash/scrub cycles without surface break or the extent of abrasion upon request</p> <p><b>VOC Class</b> Greenguard &amp; Greenguard Gold</p> <p><b>Formaldehyde Classification</b> Class E1 as per EN717-1</p> <p><b>Relevant LEED® Credit</b> EA Credit 1   MR Credit 4   MR Credit 5   MR Credit 6   IEQ Credit 3   IEQ Credit 3.2   IEQ Credit 4.6   IEQ Credit 8.1   IEQ Credit 9</p>
---	---	--