

## INNOVA DURALUX<sup>TM</sup> PLUS

Duralux<sup>TM</sup> Plus is a general-purpose fibre cement building board which can be used for many different and demanding applications. Among these are interior lining, domestic and commercial soffits, exposed beam ceilings, in wet areas and as a substrate for ceramic wall tiles. Duralux<sup>TM</sup> Plus is quick and easy to apply to timber or steel framing and is available in 3 thicknesses.

## APPLICATION

General purpose interior wet area and exterior lining.

## AUSTRALIAN STANDARDS

Manufactured to conform to the requirements of AS2908.2 Cellulose-Cement Products and are classified as Category 2 for use in applications where it will be sheltered from the weather.

Tested in accordance to AS1530.3

## INSTALLATION

Duralux<sup>TM</sup> Plus is suitable for fixing to timber and lightweight steel framing.

Duralux<sup>TM</sup> Plus can be butt jointed over framing members or with a PVC sheet holder. All sheet edges and joints must be supported by the frame. Fixing centres must not exceed 200mm on the edges of the sheet and 300mm centres in the body of the sheet. Do not place fixings closer than 12mm from sheet edges, or closer than 50mm from sheet corners. The sheet must be held firmly against the framing when fixing to ensure breakout does not occur on the back.

### Interior Wall Lining

Duralux<sup>TM</sup> Plus sheets may be fixed vertically or horizontally. Where the wall is to be tiled, fix at 200mm centres in the body of the sheet as well as along the sheet edges. Do not bridge sheet joint with tiles.

Note: Framing must support all sheet joints. When sheets are fixed adjacent to a floor, leave a 6mm gap between the bottom of the sheets and the floor.

### Wet Areas

Duralux<sup>TM</sup> Plus offers a proven, cost effective lining system for use in wet areas when installed in accordance with AS3740: 1994 'Waterproofing of wet areas within residential buildings'. Duralux<sup>TM</sup> Plus to be fitted vertically with no joints in wet areas. Duraliner<sup>TM</sup> Plus is the preferred product in wet areas.

For full details on installation of Duralux Plus for Exterior Soffits and bracing, please refer to the Duralux<sup>TM</sup> Plus brochure.

**Refer to the Duralux<sup>TM</sup> Plus brochure for complete installation instructions –**  
**[www.innovafibreceiment.com.au](http://www.innovafibreceiment.com.au)**