

Duraplank®

Weatherboards

Duraplank® combines the timeless appeal of traditional weatherboards with modern durability and ease of installation. Designed to resist decay, rot, and termite damage, this non-combustible cladding solution is built to last.

With two attractive finish options – smooth and woodgrain – Duraplank® delivers an authentic weatherboard aesthetic while offering the strength to endure the demands of everyday life.

Features and benefits

- Evokes the charm of traditional weatherboards.
- Built for longevity with high durability and resistance to rot and decay.
- Quick, simple installation: manual nailing, gun nailing or screw fixing.
- Complies with BAL-29 as required in AS 3959 – Construction of buildings in bushfire prone areas.

Thickness mm	Profile	Weight kg/lm	Width mm	Length mm	Product code	Pack size
7.5	Smooth	2.4	230	4200	4092793	120
	Smooth	3.1	300		4092794	120
	Woodgrain	2.4	230		4092796	120
	Woodgrain	3.1	300		4092797	120

Profiles



Smooth



Woodgrain





No. of weatherboards	4200 x 230	4200 x 300
	Weatherboard overlap 25mm	Weatherboard overlap 25mm
	Effective cover per weatherboard 4200 x 205mm or 0.861m ²	Effective cover per weatherboard 4200 x 275mm or 1.155m ²
1	230	300
2	435	575
3	640	850
4	845	1125
5	1050	1400
6	1255	1675
7	1460	1950
8	1665	2225
9	1870	2500
10	2075	2775
11	2280	3050
12	2485	3325
13	2690	3600
14	2895	3875
15	3100	4250
16	3305	4525
17	3510	4800
18	3715	5075
19	3920	5350
20	4125	5625