

ExoTec™ Facade Panel and System

ExoTec™ Facade Panel and System is a fully sealed, compressed facade panel installed with a proprietary fixing system. It features expressed joints and is either site-painted or pre-finished off-site. ExoTec™ Facade Panel and System is the most popular fibre cement commercial facade system.


ExoTec™ Facade Panel and System is suitable for use as an external facade, fascia or soffit on commercial buildings requiring a durable, low-maintenance and impact-resistant system, and an expressed-jointed panel look. It's suitable for either full panel or composite designs.



Product Code	Length (mm)	Width (mm)	Thickness (mm)	Weight per Unit ² (kg)	Coverage per Sheet (m ²)
402205	2,400	1,200	9	49.4	2.88
402209	3,000	1,200	9	61.8	3.6

Selling units per pack: 16 sheets or 1 each


ExoTec™ Facade Panel and System Accessories



Hardie™ Backing Strip 1,190mm

A weather seal at horizontal panel joints for use with ExoTec™ Facade Panel and System and Matrix™ Cladding.
Length: 1,190mm
Selling Unit: 10 per pack or each


305557



Hardie™ Backing Strip 2,390mm

A weather seal at horizontal panel joints for use with ExoTec™ Facade Panel and System and Matrix™ Cladding.
Length: 2,390mm
Selling Unit: 10 per pack or each


305558



Hardie™ Backing Strip 2,990mm

A weather seal at horizontal panel joints for use with ExoTec™ Facade Panel and System and Matrix™ Cladding.
Length: 2,990mm
Selling Unit: 10 per pack or each


305559



ExoTec™ Gasket Snap Strip 3,620mm long

For use with the ExoTec™ Facade Panel and System, this gasket snap strip is specially designed to clip into the ExoTec™ Top Hat at vertical facade panel joints to cover fixings to the structure and to provide an initial weather seal and drainage using a neoprene gasket.
Length: 3,620mm.
Selling Unit: 10 per pack


305556



ExoTec™ Top Hat 6,000mm long

A rolled metal section, for use with ExoTec™ Facade Panel and System, designed to span across the building structure to support facade panels and isolate differential movement of the panels from those of the structure.
124mm wide x 35mm deep x 0.75mm gauge thick.
Length: 6,000mm
Selling Unit: 45 per pack


305948



ExoTec™ Top Hat 7,200mm long

A rolled metal section, for use with ExoTec™ Facade Panel and System, designed to span across the building structure to support facade panels and isolate differential movement of the panels from those of the structure.
124mm wide x 35mm deep x 0.75mm gauge thick.
Length: 7,200mm
Selling Unit: 45 per pack


305947



Hardie™ Intermediate Top Hat 0.75mm BMT 6,000mm

A metal top hat for use with ExoTec™ Facade Panel and System for intermediate sheet support.
50mm wide face x 35mm deep x 0.75mm gauge thick.
Length: 6,000mm
Selling Unit: 50 per pack

305950



Hardie™ Intermediate Top Hat 0.75mm BMT 7,200mm

A metal top hat for use with ExoTec™ Facade Panel and System for intermediate sheet support.
50mm wide face x 35mm deep x 0.75mm gauge thick.
Length: 7,200mm
Selling Unit: 50 per pack

305949



Hardie™ Facade Washers

Facade washers used for exposed fastener fixing with ExoTec™ Facade Panel and System and Matrix™ Cladding.
Selling Unit: 1,000 per bag

305565

Notes:
All dimensions and masses provided are approximate only and subject to manufacturing tolerances.
Products are to be installed in accordance with the relevant and current Product Installation Guide and Technical Documentation.
For information relating to installation, best practices, warnings and warranties visit www.jameshardie.com.au or phone us on 13 11 03.

Key:
° Piece weight covers the physical product weight per board/sheet.