

Hardie™ Flex Sheet

Hardie™ Flex Sheet is a smooth, flat sheet that is painted on-site to create a flat panel look.

Hardie™ Flex Sheet is suitable for use as an external wall cladding, eaves or soffit lining in residential single and medium-density homes, including renovations and extensions, where a flat panel look is required. Ideal for full or composite construction designs on either timber or light gauge steel framed homes.

25
25 year warranty

Hardie™ Flex Sheet



Product Code	Length (mm)	Width (mm)	Thickness (mm)	Weight per Unit ^a (kg)	Coverage per Panel (m²)
400189	1,800	1,200	4.5*	15.0	2.16
400186	2,400	1,200	4.5*	20.0	2.88
400184	2,700	1,200	4.5*	22.5	3.24
400182	3,000	1,200	4.5*	25.0	3.60
400193	2,400	900 ^Δ	4.5*	15.0	2.16
400171	2,400	1,200	6	26.7	2.88
400169	2,700	1,200	6	30.0	3.24
400167	3,000	1,200	6	33.4	3.60








Selling units per pack: 4.5mm – 60 sheets, 30 sheets per half pack; 6mm – 30 sheets, 15 sheets per half pack.

^Δ Half packs unavailable for 900mm wide sheet.



Close-up with Hardie™ Axent™ Trim batten

Hardie™ Flex Sheet Accessories

 Hardie™ 45x45mm PVC Corner Angle Mould 3,000mm A PVC extrusion used to finish internal and external corners. Length: 3,000mm Selling Unit: 25 per pack 305554	 Hardie™ 4.5mm PVC Straight Joiner 2400mm A PVC extrusion used to join sheets. Length: 2,400mm x 4.5mm Selling Unit: 25 per pack 305538
 Hardie™ 4.5mm PVC Straight Joiner 3,000mm A PVC extrusion used to join sheets. Length: 3,000mm x 4.5mm Selling Unit: 25 per pack 305541	 Hardie™ 4.5mm PVC Cap Mould 3,000mm A PVC extrusion used to finish sheet edges. Length: 3,000mm x 4.5mm Selling Unit: 25 per pack 305542
 Hardie™ 6mm PVC External Corner Angle 3,000mm A PVC extrusion, to be used with 6mm thick sheets at external corner junctions to conceal the sheet edge. Length: 3,000mm Selling Unit: 25 per pack 305544	 Hardie™ 6mm PVC Internal Corner Angle 3,000mm A PVC extrusion, to be used with 6mm thick sheets at internal corner junctions to conceal the sheet edge. Length: 3,000mm Selling Unit: 25 per pack 305545
 Hardie™ 6mm PVC Straight Joiner 3,000mm A PVC extrusion used to join sheets. Length: 3,000mm x 6.0mm Selling Unit: 25 per pack 305546	 Hardie™ 6mm PVC Cap Mould 3,000mm A PVC extrusion used to finish sheet edges. Length: 3,000mm x 6.0mm Selling Unit: 25 per pack 305543
 Hardie™ 6mm PVC Flashing Mould 3,000mm A PVC extrusion for multicourse fixing of 6mm thick sheets. Length: 3,000mm Selling Unit: 25 per pack 305552	 Hardie™ Drive Screw 41mm Square Drive A class 3 self-tapping wing-tipped screw for fastening to 0.5mm to 1.6mm BMT light gauge steel frames. Selling Unit: 1,000 per box 305984
 Hardie™ Drive Screw 41mm Phillips Drive Collated A class 3 self-tapping wing-tipped screw for fastening to 0.5mm to 1.6mm BMT light gauge steel frames. Suitable for use in most auto feed screw guns. Selling Unit: 1,000 per box 305982	 Hardie™ Fibreshears Electric tool for cutting fibre cement sheets. Selling Unit: 1 each 300653

Notes:

All dimensions and masses provided are approximate only and subject to manufacturing tolerances.
Products are to be installed in accordance with the relevant and current Product Installation Guide and Technical Documentation.
For information relating to installation, best practices, warnings and warranties visit www.jameshardie.com.au or phone us on 13 11 03.

Key:

* 4.5mm thick sheets are not suitable for use as bracing. ° Piece weight covers the physical product weight per board/sheet.

Hardie™ Flex Eaves Lining

Hardie™ Flex Eaves Lining is a smooth, flat sheet that is produced in widths specifically made for eaves. It is site-painted to create a flat panel look.

Hardie™ Flex Eaves Lining is specifically designed to line eaves and soffits in residential single and medium-density homes, including renovations and extensions, where a flat panel look is required. It can be used on either timber or light gauge steel framed homes.









Product Code	Length (mm)	Width (mm)	Thickness (mm)	Weight per Unit* (kg)	Coverage per Sheet (m²)
400393	2,400	450	4.5	7.5	1.08
400392	2,400	600	4.5	10.0	1.44
400391	2,400	750	4.5	12.5	1.8

Selling units per pack: 60 sheets or 30 sheets

25
25 year
warranty



Hardie™ Flex Eaves Lining Accessories

 305506	Hardie™ 4.5mm PVC Eave Soffit Express Jointer 3,000mm A PVC extrusion used to join 4.5mm thick Versilux™ Lining or Hardie™ Flex Sheets in eave and soffit applications, to give an expressed joint look. Note: Not suitable for external wall cladding applications. Selling Unit: 25 per pack	 305538	Hardie™ 4.5mm PVC Straight Jointer 2,400mm A PVC extrusion used to join sheets. Length: 2,400mm x 4.5mm Selling Unit: 25 per pack
 305541	Hardie™ 4.5mm PVC Straight Jointer 3,000mm A PVC extrusion used to join sheets. Length: 3,000mm x 4.5mm Selling Unit: 25 per pack	 305432	Hardie™ 6mm PVC Eave Soffit Express Jointer 3,000mm A PVC extrusion used to join 6mm thick Versilux™ Lining or Hardie™ Flex Sheets in eave and soffit applications, to give an expressed joint look. Note: Not suitable for external wall cladding applications. Selling Unit: 25 per pack
 305546	Hardie™ 6mm PVC Straight Jointer 3,000mm A PVC extrusion used to join sheets. Length: 3,000mm x 6.0mm Selling Unit: 25 per pack	 300653	Hardie™ Fibreshears Electric tool for cutting fibre cement sheets. Selling Unit: 1 each
 305915	Villaboard™ Knife A score and snap knife designed to efficiently cut through Hardie™ external cladding and internal lining products ≤9mm thick. Selling Unit: 12 per pack	 300660	Hardie™ Blade 185mm A poly-diamond blade for fast and clean cutting of Hardie™ fibre cement products. Diameter: 185mm Selling Unit: 1 each
 303375	Hardie™ Blade 254mm A poly-diamond blade for fast and clean cutting of Hardie™ fibre cement products. Diameter: 254mm Selling Unit: 1 each		

Notes:
All dimensions and masses provided are approximate only and subject to manufacturing tolerances.
Products are to be installed in accordance with the relevant and current Product Installation Guide and Technical Documentation.
For information relating to installation, best practices, warnings and warranties visit www.jameshardie.com.au or phone us on 13 11 03.

Key:
° Piece weight covers the physical product weight per board/sheet.