

Matrix™ Cladding

Matrix™ Cladding is a pre-primed exterior cladding system with a geometric look created by an express joint which leaves a precise 10mm gap between panels.

Choose from various panel sizes to create a variety of geometric shapes in square, vertical, horizontal and brick pattern layouts.

Matrix™ Cladding panels are installed on vertical cavity battens with horizontal backing strips. They're suitable for use in residential and medium-density applications wherever a modern look is required. It brings design diversity and suits mixed cladding designs in new builds as well as upper floor and ground floor extensions.



Product Code	Length (mm)	Width (mm)	Thickness (mm)	Weight per Unit ^a (kg)	Coverage per Panel (m ²)
403811	1,190	1,190	8	18.0	1.42
403810	2,390	590	8	17.9	1.41
404169	2,990	1,190	8	45.1	3.56







25 year warranty

Selling units per pack: 30

Hardie™ Cavity Batten

405307	3,000	70	19	5.0	-
--------	-------	----	----	-----	---

Matrix™ Cladding Accessories

	Hardie™ 9mm Aluminium External Square Corner 3,000mm Aluminium extrusion that creates a square edge in external corner. Length: 3,000mm Selling Unit: 5 per pack		Hardie™ 18mm PVC Cavity Vent Strip 3,000mm A perforated PVC extrusion used at the bottom of walls behind Matrix™ Cladding. Selling Unit: 25 per pack
	Hardie™ Backing Strip 1,190mm A weather seal at horizontal panel joints for use with ExoTec™ Facade Panel and System and Matrix™ Cladding. Length: 1,190mm Selling Unit: 10 per pack or each		Hardie™ Backing Strip 2,390mm A weather seal at horizontal panel joints for use with ExoTec™ Facade Panel and System and Matrix™ Cladding. Length: 2,390mm Selling Unit: 10 per pack or each
	Hardie™ Backing Strip 2,990mm A weather seal at horizontal panel joints for use with ExoTec™ Facade Panel and System and Matrix™ Cladding. Length: 2,990mm Selling Unit: 10 per pack or each		Hardie™ Facade Washers Facade washers used for exposed fastener fixing with ExoTec™ Facade Panel and System and Matrix™ Cladding. Selling Unit: 1,000 per bag
	Hardie™ Drive Screw 41mm Square Drive A class 3 self-tapping wing-tipped screw for fastening to 0.5mm to 1.6mm BMT light gauge steel frames. Selling Unit: 1,000 per box		Hardie™ Drive Screw 41mm Phillips Drive Collated A class 3 self-tapping wing-tipped screw for fastening to 0.5mm to 1.6mm BMT light gauge steel frames. Suitable for use in most auto feed screw guns. Selling Unit: 1,000 per box
	Hardie™ Blade 185mm/254mm A poly-diamond blade for fast and clean cutting of Hardie™ fibre cement products. 185mm / 254mm Diameter: 185mm / 254mm Selling Unit: 1 each		Hardie™ Joint Sealant* 300mL cartridge A general purpose, paintable, exterior grade polyurethane joint sealant. 300mL cartridge Selling Unit: 20 per box
	Hardie™ Joint Sealant* 600mL sausage A general purpose, paintable, exterior grade polyurethane joint sealant. 600mL sausage Selling Unit: 20 per box		Hardie™ Base Coat 15kg Bag A water-resistant base coat compound. Selling Unit: 1 each

Notes:
All dimensions and masses provided are approximate only and subject to manufacturing tolerances.
Products are to be installed in accordance with the relevant and current Product Installation Guide and Technical Documentation.
For information relating to installation, best practices, warnings and warranties visit www.jameshardie.com.au or phone us on 13 11 03.

Key:
^ Hardie™ Joint Sealant is unsuitable as a fire rated sealant. ° Piece weight covers the physical product weight per board/sheet.