

Hardie™ Panel Compressed Sheet

Hardie™ Panel Compressed Sheet is a structural flooring substrate for ceramic tile finishes over timber or lightweight steel floor joists; it's made from durable compressed fibre cement.

Hardie™ Panel Compressed Sheet is suitable for use as an internal substrate for tiled wet-area floors and an external substrate for tiled balconies, verandas and decks, in both residential and commercial buildings. It's a durable, moisture-resistant alternative to particleboard and plywood substrates, and a lightweight alternative to concrete.



Product Code	Length (mm)	Width (mm)	Thickness (mm)	Weight per Unit [°] (kg)	Coverage per Panel (m ²)
--------------	-------------	------------	----------------	-----------------------------------	--------------------------------------

Hardie™ Panel Compressed Sheet 15mm^Δ

400081	2,400	1,200	15 ^Δ	80.4	2.88
400079	3,000	1,200	15 ^Δ	100.5	3.6

Hardie™ Panel Compressed Sheet 18mm^Δ

400094	2,400	1,200	18 ^Δ	96.5	2.88
400460	3,000	1,200	18 ^Δ	120.6	3.6

Hardie™ Panel Compressed Sheet 24mm^Δ

400461	2,400	1,200	24 ^Δ	128.6	2.88
--------	-------	-------	-----------------	-------	------

Selling units per pack: 15mm – 10 sheets or each; 18mm – 8 sheets or each; 24mm – 6 sheets or each

Key:

^Δ Unavailable in WA. [°] Piece weight covers the physical product weight per board/sheet.



25 year warranty

Hardie™ Panel Compressed Sheet Accessories



305554

Hardie™ 45x45mm PVC Corner Angle Mould 3,000mm

A PVC extrusion used to finish internal and external corners.
Length: 3,000mm
Selling Unit: 25 per pack



300660

Hardie™ Blade 185mm

A poly-diamond blade for fast and clean cutting of Hardie™ fibre cement products.
Diameter: 185mm
Selling Unit: 1 each



303375

Hardie™ Blade 254mm


A poly-diamond blade for fast and clean cutting of Hardie™ fibre cement products.
Diameter: 254mm
Selling Unit: 1 each



305534

Hardie™ Joint Sealant* 300mL cartridge

A general purpose, paintable, exterior grade polyurethane joint sealant.
300mL cartridge
Selling Unit: 20 per box



305672

Hardie™ Joint Sealant* 600mL sausage

A general purpose, paintable, exterior grade polyurethane joint sealant.
600mL sausage
Selling Unit: 20 per box

Notes:
All dimensions and masses provided are approximate only and subject to manufacturing tolerances.
Products are to be installed in accordance with the relevant and current Product Installation Guide and Technical Documentation.
For information relating to installation, best practices, warnings and warranties visit www.jameshardie.com.au or phone us on 13 11 03.

Key:
^ Hardie™ Joint Sealant is unsuitable as a fire rated sealant.